




**INSTRUCTIONS AND  
RECOMMENDED PARTS  
FOR MAINTENANCE**

GEI-28838I  
Supersedes GEI-28838H

**INSTALLATION OF PRIMARY CABLES  
IN METAL-ENCLOSED SWITCHGEAR**



**SWITCHGEAR PRODUCTS DEPARTMENT**

**GENERAL  ELECTRIC**

**PHILADELPHIA, PA.**

(c) Remove the pothead from the unit, disassemble the wiping sleeve and slip it and its gasket over the cable as shown in Fig. 4.

(d) Remove the lead sheath from the cable to the point marked in operation "b" as shown in Figs. 5 and 6 proceeding as follows:

First, make a cut around the cable half through the sheath at the reference point. Second, split the sheath lengthwise between the cut and the cable, holding the cutting tool at an angle to the cable radius to avoid damaging the insulation. Third, remove the sheath by catching the split edge with pliers and pulling directly away from the cable axis.

Clean and tin the outside of the lead sheath for about 3 inches and bell out the end of the lead sheath.

(e) Remove the belt and interphase insulation down to within 1-1/2 inches of the lead sheath as shown in Fig. 7. The last few layers should be torn off to avoid damaging the individual conductor insulation. To reinforce and protect the conductor insulation, wrap two layers of half lapped varnished cambric or irrathene tape over the factory insulation.

(f) Disassemble insulator support plate from pothead body. The insulators should not be removed from the support plate because they are factory assembled for proper compression of their gaskets. Place pothead body over cable and then fan out the conductors into approximately the final position, as shown in Figs. 8 and 9. The middle conductor should be bowed slightly for final adjustment of length. Avoid sharp bends and damage to the insulation, particularly at the crotch.

(g) For system voltage above 7500 volts it is recommended that stress relief cones be built up when single-conductor or three-conductor shielded cable is used. Construct stress relief cones in accordance with the recommendations of the cable manufacturer. See Fig. 1 for one recommended method. On lower voltage cables, belling out the end of the lead sheath ordinarily provides sufficient stress relief. (Stress cone material will not be furnished with pothead).

(h) Bolt pothead body to metal-clad adapter plate. Shape conductors into final position, then cut off each conductor to fit its terminal.

(i) Remove pothead terminals from insulators. Remove two inches of insulation from the end of each conductor and assemble pothead terminals to cables.

(j) Assemble gaskets where shown in Fig. 1 and bolt insulator support plate and wiping sleeve to pothead body. Compress gaskets by a partial turn on each bolt successively until the gasket is uniformly compressed to dimensions shown in Fig. 1. Check to be sure the terminal studs are seated properly on their gaskets, then screw contact nut in place after assembling top gaskets and washers. See Figs. 9, 10 and 11.



Fig. 4



Fig. 5




Fig. 6



Fig. 7



Fig. 8



Fig. 9



Fig. 10



Fig. 11

Fig. 4 (857623)  
Fig. 5 (857622)

Fig. 6 (857621)  
Fig. 7 (857618)

Fig. 8 (857611)  
Fig. 9 (857608)

Fig. 10 (857619)  
Fig. 11 (857610)

(k) Make a plumber's wiped joint between the wiping sleeve and the lead sheath of the cable, as shown in Figs. 12 and 13.

(l) Remove the 3/4" filling plug in the pothead body, the pipe plugs in the top of the studs and in the insulator support plate. Insert a stand pipe and funnel in the filling hole of sufficient height to extend above the top of the studs as shown in Fig. 14.

Heat compound to the pouring temperature, 165 C. for #227 or 135-160 C for novoid "X". Do not overheat compound as higher temperatures may injure cable insulation and also result in excessive shrinkage of the compound while cooling. Before and while filling, warm pothead body and stand pipe to prevent sudden chilling of compound which may result in the formation of air voids. The pothead may be warmed by playing a blowtorch over the body, taking care that no direct heat reaches the porcelain or gaskets.

Pour until the compound appears at the insulator support plate plug holes. Insert plugs and continue filling until it appears at holes at the top of terminal studs. Insert plugs and continue pouring while the pothead and compound cools to fill air voids which might form.

When the pothead has cooled, remove filling pipe and insert plug. Clean off compound which might have overflowed on the outside of the porcelain.

(m) Assemble pothead connection bars (see Fig. 15), and insulate connections as follows:

(1) Fill all cavities around bolts and nuts with Duxseal compound to form smooth surface for taping, thus preventing air voids. This compound is not an insulating medium and should not be used for that purpose.

(2) Wrap with insulating tape, as shown in Fig. 19, the number of layers depending on the voltage rating of the equipment and the type of tape used. Where there are sharp angles, apply additional layers to obtain the equivalent of the insulation of the flat surfaces.

(3) Over the insulating tape, apply one layer of white cotton tape, half lap, as a binder.

(4) Over the white cotton tape, brush a good coat of varnish (U-310 for 15 KV and U-311 for 5 KV). Varnish may be thinned if necessary, with Xylene, D5B9.

#### Single-Conductor Potheads

The procedure for installation of single-conductor potheads is in general the same as described for three-conductor potheads. Refer to Fig. 20.



Fig. 12



Fig. 13




Fig. 14



Fig. 15

#### Cable Entrances Other Than Wiping Sleeve

Stuffing box cable entrance fittings are used for cables other than lead sheathed. These fittings may be provided with or without armor clamps as necessary.

The fitting consists of a cast and machined base, one or more rubber or neoprene washers, and a packing nut which compresses the washers around the cable. These parts should be assembled on the cable in the above order, with the base nearest to the pothead. The packing nut should be tightened after the cable is located in the pothead and before any compound is poured.

Where an armor clamp is required, it is usually made an integral part of the packing nut. This requires that the packing nut and the armor clamp be tightened on the cable

before the assembly of the pothead is completed.

#### Cable Sheath or Conduit Grounding

Where three-conductor conducting sheath or shielded cables are used, or where non-conducting sheath cable is carried in metallic ducts or conduits, it is usually desirable that both ends of the cable sheath or conduit be grounded directly to the switchgear ground bus or structure or other apparatus. In some cases this may be accomplished by the mounting of potheads or terminating fittings on a grounded support. When such mounting cannot be arranged, a separate ground wire should be connected between the cable sheath or conduit and the switchgear ground bus.

Where single conductor conducting sheath cables are used, the same procedure





Fig. 16 Stuffing Box (with or without Clamping Ring)



Rated kv Phase to Phase	Dimensions in Inches	
	A *	B
2 to 5	5	2
6 to 10	9	3
11 to 15	13	4

\* For ungrounded neutral use 1.33 times the dimensions in selecting distance A.

Fig. 17 Termination Non-Leaded Cable Single-Conductor

should be observed, except that only one end of the sheath should be grounded. This also applies to single conductor non-conducting sheath cables in separate metallic conduits. Where three phases are carried by single conductors in a common metallic conduit, grounding procedure should be the same as that described for three conductor cables.

#### TERMINATION NONLEADED CABLE SINGLE-CONDUCTOR

1. Cut cable to proper length.
2. Remove jacket and cable tape for distance of A plus B plus 3 inches, plus length to be inserted into terminal lug.
3. Unwrap shielding tape to point M, cut and solder it in place avoiding excessive heat on insulation. Remove outer semi-conducting tape for same distance. Thoroughly clean surface from which the semi-conducting tape was removed.
4. Remove insulation and inner semi-conducting tape to expose conductor for distance of one inch plus length to be inserted into terminal lug.
5. Attach terminal lug to conductor.
6. Taper insulation for one inch as shown.
7. Apply end seal. Clean surface over which splicing tape is to be applied and coat with G-E No. A50P68 adhesive cement or equivalent. When solvent evaporates, build up with splicing tape GE8380 or equivalent, as shown.
8. Build stress cone. Clean cable surface and coat with G-E No. A50P68 adhesive cement or equivalent. When solvent evaporates, build up cone with splicing tape GE8380 or equivalent, for length B plus B. Between points M and P, tape is applied so that wrapped thickness at N is equal to 75% of the original insulation thickness - and so that the cone tapers to zero thickness at points M and P. Apply one layer No. 33 Scotch tape or equivalent, half lapped. Obtain a smooth wrapping but do not stretch tape more than necessary.

9. Pass a turn of tightly drawn braid around exposed portion of shielding tape at point M and solder in place. Then apply shielding braid in tightly drawn 1/16 inch lap wrappings to point N and spot solder. Terminate the braid by cutting 1/2 inch beyond soldering point. Turn down and solder loose ends to preceding turns. Wrap four to six turns of No. 19 AWG tinned copper wire around shielding braid and solder. Solder all turns of braid together along three lengthwise lines equally spaced around braided surface.

10. Solder-attach ground strip to shielding tape near cable covering. Cover stress cone with one layer No. 33 Scotch tape, half lapped. Obtain a smooth wrapping but do not stretch tape more than necessary. Add two layers of splicing tape.

11. Pencil jacket for 1/2 inch as shown. Clean surface. Take particular care in cleaning outside jacket surface in order to entirely remove black wax finish. Coat with G-E No. A50P68 adhesive cement or equivalent. When solvent evaporates, apply splicing tape GE8380 or equivalent and




Fig. 18 Termination Non-Leaded Cable Multi-Conductor

make sheath seal as shown on drawing. Apply one layer No. 33 Scotch tape or equivalent, half lapped. Obtain a smooth wrapping but do not stretch tape more than necessary.

12. Over entire termination, apply two layers of No. 33 Scotch tape or equivalent, half lapped, in manner to shed water. Obtain a smooth wrapping but do not stretch tape more than necessary.

#### TERMINATION NONLEADED CABLE MULTI-CONDUCTOR

Make termination as indicated for single-conductor except - substitute the following for paragraphs 10, 11 and 12.

Pencil Geoprene jacket 1/2 inch. Clean surface over which sheath moisture seal is to be applied. Take particular care in cleaning outside jacket surface in order to entirely remove black wax finish. Coat with G-E No. A50P68 adhesive cement or equivalent. Allow to dry. Apply splicing tape GE8380 or equivalent to make moisture seal as shown. This is done by starting wrapping tape near end of jacket and wrapping over ground wires for 1-1/2 inches. Bend ground wires out and back over taping just applied and continue applying lap-

to indicate their phase relationship with the switchgear connections. This is necessary to insure that motors will rotate in the proper direction and that the phase rotation is the same when interconnecting two different sources of power.


No insulation materials are furnished for cable terminations and/or bar connections furnished by the customer. In all cases carefully follow the cable manufacturer's recommendations for installation of the type of cable being used.

## Insulating Primary Cable Terminations

All field assembled joints for primary cable terminations should be prepared as outlined under "CONNECTIONS" in GEH-1802, items 1, 2, 3 and 4 for METAL CLAD SWITCHGEAR. Upon completion of the cable termination, care must be exercised when taping the exposed termination.

If the cable is aluminum, the conductor surface must be carefully abraided and the cable covered liberally with a joint com-

- (1) Check to see that a sufficient area of insulating tape extends beyond the painted glass tape furnished by the factory. (2" for 5KV, 3" for 15KV). It may be necessary to remove the current transformer primary conductor insulating support to obtain proper insulation joint overlap. Replace support upon completion of joint. Refer to Figure 19.
- (2) All terminations should be insulated as outlined in table figure 19 for correct layers of insulating and glass tape.
- (3) The instructions for application of the tape insulation is the same as outlined for "Taped Joints" items 1, 2, 4, 6 and 7. (GEH-1802)



NOTE 1:  
I-202 & V.C. - One layer, wound 2/3 lap requires 3 turns around bar in one width of tape. One layer thickness is 3 times tape thickness.  
GLASS: - One layer, wound 1/2 lap requires 2 turns around bar in one width of tape. One layer thickness is 2 times tape thickness.

NOTE 2:  
Irrathene #202, width 1 1/2" thickness 0.010". Keep tension on tape at all times while applying.

NOTE 3:  
Glass #2L12B width 1 1/2" thickness 0.004".

NOTE 4:  
Varnished cambric A22A11a (#992) width 1 1/2", thickness 0.012".

VENT PLUG

STUD 3-12THD'S

CONTACT NUT WASHER

VENT HOLE

GASKETS

PORCELAIN INSULATOR

PRESSURE CLAMP

CLAMP

GASKET

MOUNTING SURFACE

GASKET

WIPING SLEEVE

CUT WIPING SLEEVE TO SIZE OF CABLE

50-50 WIPE

LEAD SHEATH

EXTEND TAPE INSULATION OVER PORCELAIN AS SHOWN

FINISH WITH 10MIL INSULATING TAPE 4 LAYERS 1/2 LAP. PAINT WITH STERLING U-310 VARNISH

BUILD UP WITH 10MIL 3/4 V.C. TAPE. CENTER OF BUILDUP TO HAVE 75% MORE TAPE THAN ORIGINAL

3/4 COPPER BRAID TO BE CUT AT AN ANGLE OF 15° & SOLDERED TO COPPER SHIELD. TAPE ON CABLE BRAID TO BE WOUND TIGHT & CLOSE. ALL TURNS OF BRAID TO BE SOLDERED ALONG TWO LINES PARALLEL TO CABLE TO PREVENT SEPARATION. COPPER BRAID TO BE WOUND AROUND METALLIC BINDER AND SOLDERED BOTH TO BINDER AND LEAD SHEATH

USE 3/4 GAL G.E. COMPOUND AS FURNISHED, TO FILL POTHEAD AFTER MAKING CONNECTIONS

**Figure 20 Single-Conductor Pothead Assembly**

# GENERAL ELECTRIC INSTALLATION AND SERVICE ENGINEERING OFFICES

## FIELD SERVICE OFFICE CODE KEY

- \* Mechanical & Nuclear Service
- † Electrical & Electronic Service
- ‡ Marine Service
- X Transportation

FOR YOUR LASTING SATISFACTION... with the performance and availability of your General Electric equipment, GE provides this nationwide network of field service offices, serving utility, industrial, transportation and marine users. Qualified field engineers provide installation, start-up, employee training, engineering maintenance and other services, throughout the productive life of the equipment. For full information, call your nearest Installation & Service Engineering office.

**ALABAMA**  
\* † Birmingham 35205 . . . . . 2151 Highland Ave.  
\* † Mobile 36609 . . . . . 1111 S. Beltline Highway

**ALASKA**  
† Anchorage 99501 . . . . . 115 Whitney Rd.

**ARIZONA**  
\* † Phoenix 85012 . . . . . 3550 N. Central Ave.  
† Tucson 85718 . . . . . 151 S. Tucson Blvd.

**ARKANSAS**  
† North Little Rock 72119 . . . . . 120 Main St.

**CALIFORNIA**  
\* † Los Angeles 90054 . . . . . 212 N. Vignes St.  
† Palo Alto 94303 . . . . . 960 San Antonio Rd.  
† Sacramento 95808 . . . . . 2407 J St.  
† San Diego 92103 . . . . . 2580 First Ave.  
\* † San Francisco 94119 . . . . . 55 Hawthorne St.  
\* † Vernon 90058 . . . . . 3035 E. 46th St.

**COLORADO**  
\* † Denver 80208 . . . . . 201 University Blvd.

**CONNECTICUT**  
\* † Meriden 06450 . . . . . 1 Prestige Dr.

**FLORIDA**  
† † Jacksonville 32203 . . . . . 4040 Woodcock Dr.  
† † Miami 33134 . . . . . 4100 W. Flagler St.  
\* † Tampa 33609 . . . . . 2108 S. Lois Ave.

**GEORGIA**  
\* † Atlanta 30309 . . . . . 1860 Peachtree Rd., NW  
† Savannah 31405 . . . . . 5002 Paulsen St.

**HAWAII**  
\* † Honolulu 96813 . . . . . 440 Coral St.

**ILLINOIS**  
\* † X Chicago 60680 . . . . . 840 S. Canal St.

**INDIANA**  
† Evansville 47705 . . . . . 2709 Washington Ave.  
† Fort Wayne 46807 . . . . . 3608 S. Calhoun St.  
\* † Indianapolis 46207 . . . . . 3750 N. Meridian St.

**IOWA**  
† Davenport 52805 . . . . .  
P. O. Box 630, 1039 State St., Bettendorf

**KENTUCKY**  
† Louisville 40218 . . . . . 2300 Meadow Dr.

**LOUISIANA**  
† Baton Rouge 70806 . . . . . 8312 Florida Blvd.  
\* † New Orleans 70125 . . . . . 4747 Earhart Blvd.  
\* † Shreveport 71104 . . . . . 2620 Centenary Blvd.  
† Monroe 71201 . . . . . 1028 North 8th St.

**MARYLAND**  
\* † Baltimore 21201 . . . . . 1 N. Charles St.

**MASSACHUSETTS**  
\* † Welleley 02181 . . . . . 1 Washington St.

**MICHIGAN**  
\* † Detroit 48202 . . . . . 700 Antoinette St.  
† Jackson 49201 . . . . . 210 W. Franklin St.  
† Saginaw 48607 . . . . .  
1008 Second National Bank Bldg.

**MINNESOTA**  
\* † Duluth 55802 . . . . . 300 W. Superior St.  
\* † Minneapolis 55416 . . . . . 1500 Lilac Drive So.

**MISSOURI**  
\* † Kansas City 64199 . . . . . 911 Main St.  
\* † St. Louis 63101 . . . . . 1015 Locust St.

**MONTANA**  
† Butte 59701 . . . . . 103 N. Wyoming St.

**NEBRASKA**  
\* † Omaha 68102 . . . . . 409 S. 17th St.

**NEW JERSEY**  
\* † Millburn 07041 . . . . . 25 E. Willow St.

**NEW YORK**  
† Albany 12205 . . . . . 15 Computer Drive, West  
\* † Buffalo 14205 . . . . . 825 Delaware Ave.  
\* † X New York 10022 . . . . . 641 Lexington Ave.  
\* † Rochester 14604 . . . . . 89 East Ave.  
\* † Syracuse 13206 . . . . . 3532 James St.

**NORTH CAROLINA**  
\* † Charlotte 28207 . . . . . 141 Providence Rd.  
\* † Wilmington . . . . .  
Reigelwood 28456 . . . . . P. O. Box 186

**OHIO**  
\* † Cincinnati 45206 . . . . . 2621 Victory Pkwy.  
\* † Cleveland 44104 . . . . . 1000 Lakeside Ave.  
† Columbus 43229 . . . . . 1110 Morse Rd.  
† Toledo 43606 . . . . . 325 Douglas Rd.  
† Youngstown 44507 . . . . . 272 Indianola Ave.

**OKLAHOMA**  
\* † Oklahoma City 73108 . . . . . 2000 Classen Blvd.  
† Tulsa 74105 . . . . . P. O. Box 7648, Southside Sta.

**OREGON**  
† Eugene 97401 . . . . . 1170 Pearl St.  
\* † Portland 97210 . . . . . 2929 NW 29th Ave.

**PENNSYLVANIA**  
\* † Allentown 18102 . . . . . 1444 Hamilton St.  
\* † Philadelphia 19102 . . . . . 3 Penn Center Plaza  
\* † Pittsburgh 15222 . . . . . 300 6th Avenue Bldg.

**SOUTH CAROLINA**  
† Columbia 29204 . . . . . 2700 Middleburg Dr.  
† Greenville 29607 . . . . . 41 N. Pleasantburg Dr.

**TENNESSEE**  
\* † Chattanooga 37411 . . . . .  
5800 Bldg, Eastgate Center  
† Memphis 38130 . . . . . 3385 Airways Blvd.

**TEXAS**  
\* † Amarillo 79101 . . . . . 303 Polk St.  
\* † Beaumont 77704 . . . . . 1385 Calder Ave.  
\* † Corpus Christi 78401 . . . . . 205 N. Chaparral St.  
† Dallas 75222 . . . . . 8101 Stemmons Freeway  
† El Paso 79945 . . . . . 215 N. Stanton  
† Fort Worth 76102 . . . . . 408 W. Seventh St.  
† Houston 77027 . . . . . 4219 Richmond Ave.  
† San Antonio 78204 . . . . . 434 S. Main St.

**UTAH**  
† Salt Lake City 84111 . . . . . 431 S. Third East St.

**VIRGINIA**  
† Newport News 23601 . . . . . 311 Main St.  
† Richmond 23230 . . . . . 1508 Willow Lawn Dr.  
† Roanoke 24015 . . . . . 2018 Colonial Ave.

**WASHINGTON**  
\* † Seattle 98188 . . . . .  
112 Andover Park East, Tukwila  
† Spokane 99202 . . . . . E. 1805 Trent Ave.

**WEST VIRGINIA**  
\* † Charleston 25328 . . . . . 306 MacCorkle Ave., SE

**WISCONSIN**  
\* † Appleton 54911 . . . . . 3003 West College Dr.  
† Milwaukee 53202 . . . . . 615 E. Michigan St.

## GENERAL ELECTRIC SERVICE SHOPS

WHEN YOU NEED SERVICE... These GE Service Shops will repair, recondition, and rebuild your electric apparatus. The facilities are available day and night, seven days a week, for work in the shops or on your premises.

Latest factory methods and genuine GE renewal parts are used to maintain performance of your equipment. For full information about these services, contact your nearest service shop or sales office.

**ALABAMA**  
\* † Birmingham 35211 . . . . . 1500 Mims Ave., S.W.  
\* † Mobile 36609 . . . . . 721 Lakeside Dr.

**ARIZONA**  
\* (Phoenix) Glendale 85019 . . . . . 4911 W. Colter St.  
\* † Phoenix 85019 . . . . . 3640 W. Clarendon St.  
\* † Tucson 85713 . . . . . 2942 So. Palo Verde Ave.

**CALIFORNIA**  
\* † Los Angeles 90301 . . . . . 6900 Stanford Ave.  
\* (Los Angeles) Anaheim 92805 . . . . .  
3601 E. La Palma Ave.  
\* (Los Angeles) Inglewood 90301 . . . . .  
228 W. Florence Ave.  
\* † Sacramento 95814 . . . . . 99 North 17th St.  
\* (San Francisco) Oakland 94608 . . . . .  
1650 34th St.

**COLORADO**  
\* † Denver 80205 . . . . . 3353 Larimer St.

**CONNECTICUT**  
\* † (Southington) Plainville 06479 . . . . .  
370 Atwater St.

**FLORIDA**  
\* † Jacksonville 32203 . . . . . 2020 W. Beaver St.  
\* (Miami) Hialeah 33010 . . . . . 1062 East 28th St.  
\* † Tampa 33601 . . . . . 19th & Grant Sts.

**GEORGIA**  
\* (Atlanta) Chamblee 30341 . . . . .  
5035 Peachtree Industrial Blvd.  
\* † Atlanta . . . . . 2379 John Glenn Dr.

**ILLINOIS**  
\* † Chicago 60638 . . . . . 6045 S. Nottingham Ave.

**INDIANA**  
† Evansville 47711 . . . . . 401 N. Congress Ave.  
† Ft. Wayne 46803 . . . . . 1731 Edsall Ave.  
† Hammond 46320 . . . . . 1138 104th Place  
† Indianapolis 46222 . . . . . 1740 W. Vermont St.

**IOWA**  
\* (Davenport) Bettendorf 52722 . . . . . 1025 State St.

**KENTUCKY**  
\* † Louisville 40209 . . . . . 3900 Crittenden Drive

**LOUISIANA**  
\* † Baton Rouge 70814 . . . . . 10955 North Dual St.  
\* † New Orleans 70114 . . . . . 1115 DeArmas St.

**MARYLAND**  
\* † Baltimore 21230 . . . . . 920 E. Fort Ave.

**MASSACHUSETTS**  
\* † (Boston) Medford 02155 . . . . .  
3960 Mystic Valley Pkwy.

**MICHIGAN**  
\* † (Detroit) Riverview . . . . . 18075 Krause Ave.  
\* † Flint 48505 . . . . . 1506 E. Carpenter Rd.

**MINNESOTA**  
\* † Duluth 55807 . . . . . 50th Ave. W. & St. Louis Bay  
\* † Minneapolis 55430 . . . . . 2025 49th Ave., N.

**MISSOURI**  
\* † Kansas City 64120 . . . . . 3525 Gardner Ave.  
\* † St. Louis 63110 . . . . . 1115 East Rd.

**NEW JERSEY**  
\* † New Brunswick 08902 . . . . . 3 Lawrence St.

**NEW MEXICO**  
\* † Albuquerque 87109 . . . . . 4420 McLeod Rd. NE

**NEW YORK**  
\* † Albany 12205 . . . . . 1097 Central Ave.  
\* (Buffalo) Tonawanda 14150 . . . . . 175 Milens Rd.  
\* (Long Island) Old Bethpage 11804 . . . . .  
183 Bethpage-Sweet Hollow Rd.  
\* (New York City) North Bergen, N.J. 07012 . . . . .  
6001 Tonnelle Ave.  
\* (New York City) Clifton, N.J. 07012 . . . . .  
9 Brighton Rd.  
\* † Schenectady 12305 . . . . . 1 River Rd.  
\* † Syracuse 13208 . . . . . 1015 E. Hiawatha Blvd.

**NORTH CAROLINA**  
\* † Charlotte 28208 . . . . . 2328 Thrift Rd.

**OHIO**  
\* † Akron (Canton) 44720 . . . . . 7900 Whipple Ave. N. W.  
\* † Cincinnati 45202 . . . . . 444 West 3rd St.  
\* † Cleveland 44125 . . . . . 4477 East 49th St.  
\* † Columbus 43229 . . . . . 6860 Huntley Rd.  
\* † Toledo 43605 . . . . . 405 Dearborn Ave.  
\* † Youngstown 44507 . . . . . 272 E. Indianola Ave.

**OKLAHOMA**  
\* † Tulsa 74145 . . . . . 5220 S. 100th East Ave.

**OREGON**  
\* † Eugene 97402 . . . . . 570 Wilson St.  
\* † Portland 97210 . . . . . 2727 NW 29th Ave.

**PENNSYLVANIA**  
\* † Allentown 18103 . . . . . 686 E. Highland St.  
\* (Delaware Valley) Cherry Hill, N.J. 08034 . . . . .  
1790 E. Marlton Pike  
\* † Johnstown 15802 . . . . . 841 Oak St.  
\* † Philadelphia 19124 . . . . . 1040 East Erie Ave.  
\* (Pittsburgh) West Mifflin 15122 . . . . .  
4930 Buttermilk Hollow Rd.  
\* † York 17403 . . . . . 54 N. Harrison St.

**SOUTH CAROLINA**  
\* (Charleston) No. Charleston 29401 . . . . .  
2490 Debonair St.

**TENNESSEE**  
\* † Knoxville 37914 . . . . .  
2621 Governor John Sevier Hwy.  
\* † Memphis 38107 . . . . . 708 North Main St.

**TEXAS**  
\* † Beaumont 77705 . . . . . 1490 W. Cardinal Dr.  
\* † Corpus Christi 78401 . . . . . 115 Waco St.  
\* † Dallas 75235 . . . . . 3202 Manor Way  
\* † Houston 77036 . . . . . 5534 Harvey Wilson Dr.  
\* † Houston 77036 . . . . . 6916 Harwin Dr.  
\* † Midland 79701 . . . . . 704 S. Johnston St.

**UTAH**  
\* † Salt Lake City 84110 . . . . . 301 S. 7th West St.

**VIRGINIA**  
\* † Richmond 23224 . . . . . 1403 Ingram Ave.  
\* † Roanoke 24013 . . . . . 1004 River Ave., SE

**WASHINGTON**  
\* † Seattle 98134 . . . . . 3422 First Ave., South  
\* † Spokane 99211 . . . . . E. 4323 Mission St.

**WEST VIRGINIA**  
\* † Charleston 25328 . . . . . 308 MacCorkle Ave., SE

**WISCONSIN**  
\* (Appleton) Menasha 54910 . . . . . 1725 Racine St.  
\* † Milwaukee 53207 . . . . . 235 W. Oklahoma Ave.

\* Electrical/Mechanical Service Shop \* Instrumentation Shop Δ Special Manufacturing Shop