



WESTINGHOUSE TERMINAL BLOCKS are designed to meet modern demands of space economy, safety in operation, and flexibility in arrangement of control wiring and conduits. Black Moldarta blocks are compact, sturdy, and serviceable; they can be mounted by any two of the four bolt holes provided. Maximum short circuit protection is provided between wires and to ground. Westinghouse terminal blocks are rated 30 to 50 amperes. Test voltages greatly in excess of AIEE requirements for 750-volt service can be successfully applied.

STANDARD MOLDARTA BLOCKS are formed of a plastic material of fibrous celluose filler and synthetic resin binder. They have exceptionally high resistance to heat, moisture, and shock. This material is resistant to common solvents and has a smooth, even finish which tends to retard the accumulation of dust.

REVERSIBLE MARKING STRIPS, black on one side and light tan on the other, are standard. Labelling the circuits may be done on the light tan side with ink or black paint, and on the black side with yellow or white paint. A 3/16 inch thick marking

strip black on both sides can be supplied on request without extra charge.

**COVERS** are optional. If used, they can be removed without disturbing mounting or connections by partially unscrewing the inner screws and slipping the cover out from beneath the marking strip.

HARDWARE is furnished complete with all blocks. Terminal screws, terminals, and washers are tinned to prevent corrosion. All hardware will withstand mechanical and electrical stresses encountered in ordinary duty.

Standard terminals are suitable for wire sizes No. 18 to No. 10 maximum. High pressure terminals are available for wire sizes No. 20 to No. 6 maximum.

MOUNTING is done simply by placing the blocks flat on the housing or panel, or on brackets with axis perpindicular to the mounting surface. All blocks are drilled for either bracket or flat mounting.

#### **WESTINGHOUSE SPECIAL FEATURES**

- 1 EASE OF MOUNTING—Blocks can be mounted flat on housing or panel, or on brackets, by any two of four bolt holes.
- REVERSIBLE MARKING STRIPS can be lettered with white or yellow paint on the black side, or with ink or black paint on the light tan side.

- **REMOVABLE COVERS**, when used, can be removed without disturbing mounting, connections, or marking strips.
- MOLDARTA PLASTIC BLOCKS resist heat, moisture, shock, and common solvents. Smooth finish retards accumulation of dust.

Supersedes Catalog Section 37-260 dated October 30, 1951


**JANUARY 31, 1952** 

## LIST PRICES—TERMINAL BLOCKS-

#### STANDARD TERMINALS BLOCKS

Dimensions are approximate only.

Do not use for construction purposes.




8-circuit terminal block with light tan side of reversible marking strip showing.

	NO. OF CIRCUITS	STYLE NUMBER*	DIMENSIONS IN INCHES‡		WT. LBS.	LIST PRICE	
			A	В	EACH	CARTON OF 10†	STD. PKG. OF 50
WITHOUT COVER							
	4 5 8 12	1170 851 542 245 542 246 542 247	35/8 45/16 63/8 91/8	3½ 31¾ 5½ 85%	1/2 3/4 1 1/2	\$10.80 10.80 19.40 26.00	\$ 48.60 48.60 87.30 117.00
WITH COVER							
	4 5 8 12	1170 852 1123 963 1123 964 1123 965	35% 45% 63% 91%	31/8 313/16 57/8 85/8	3/4 1 11/2 2	19.40 19.40 29.00 36.30	87.30 87.30 130.00 163.00

## TERMINAL BLOCKS WITH HIGH PRESSURE CONNECTORS

Dimensions are approximate only. Do not use for construction purposes.



8-circuit terminal block complete with marking strip and high pressure connectors.


These terminal blocks are the same as the standard type except for hardware. High pressure connectors eliminate handling and use of miscellaneous hardware. The connector screws are turned partly out to permit easy insertion of one or more wires.

	NO. OF CIRCUITS	STYLE NUMBER*	DIMENSIONS IN INCHEST		WT. LBS,	LIST PRICE	
			A B	В	EACH	CARTON OF 10†	STD. PKG. OF 50
WITHOUT COVER							
	4 5 8 12	1196 115 1196 116 1196 117 1196 118	3 % 45% 6 % 9 %	3½ 3½ 5½ 5½ 85%	1½ 1½ 2½ 3	\$13.39 13.30 24.20 32.60	\$60.00 60.00 109.00 147.00
	WITH COVER						
	4 5 8 12	1491 642 ① 1491 643 ① 1491 644 ① 1491 645 ①	3% 4% 6% 9%	3½ 313/ <sub>16</sub> 5½ 85/8	1½ 1¾ 3 3½	23.00 23.00 33.90 42.40	103.00 103.00 153.00 191.00


#### MOUNTING BRACKETS (Complete Bracket for 8 and 12-Circuit Terminal Blocks)

TYPE OF MOUNTING	STYLE NUMBER	LIST PRICE FOR CARTON OF 6†
Steel panel or channel frame Panel or pipe frame mounting Panel or angle frame mounting	1446 993 1446 994 1446 995	\$9.40 9.40 9.40
*Style Nos include hardware and marking strip. † Do not order less than a	anton guantita † Mounting h	oles are 201 inch in diameter

# METHODS OF MOUNTING



Terminal blocks mounted on single angle bracket with axis perpendicular to panel.



Terminal blocks mounted flat. Note cleats on wiring to prevent loosening of terminals on block.



WESTINGHOUSE ELECTRIC CORPORATION EAST PITTSBURGH PLANT . SWITCHGEAR DIVISION . EAST PITTSBURGH, PA.