

II. ADJUSTMENTS

- 21P - Differential balance for the operational amplifier.
- 22P - Common mode balance for the operational amplifier.

III. SPECIFICATIONS AND RATINGS

Transfer function:
$$\frac{V'_c}{v_b} = \frac{64}{1 + p0.1}$$

Ambient Temperature: 0 to 55°C

Bias: When $v_b = -v_b^* = 0$


Power Requirements: PSP: +24V \pm 0.5V ... 30mA

Then $V'_c = +7V$

PSN: -24V \pm 0.5V ... 34mA

Output:

LOAD	OUTPUT SWING
C-56 GPG	$V'_c = +14V, -12V$
1.8K OHM	$V'_c = +14V, -13V$



PC CARD (Front View)

II. ADJUSTMENTS

- 21P - Differential balance for the operational amplifier.
- 22P - Common mode balance for the operational amplifier.

III. SPECIFICATIONS AND RATINGS

Transfer function: $\frac{V'_c}{v_b} = \frac{64}{1 + p0.1}$

Ambient Temperature: 0 to 55°C

Power Requirements: PSP: +24V \pm 0.5V ... 30mA


Bias: When $v_b = -v_b^* = 0$

PSN: -24V \pm 0.5V ... 34mA

Then $V'_c = +7V$

Output:

LOAD	OUTPUT SWING
C-56 GPG	$V'_c = +14V, -12V$
1.8K OHM	$V'_c = +14V, -13V$



PC CARD (Front View)